## DATA SHEET – HPU015 HYDRAULIC POWER UNIT



### **Overview**

Pressure Dynamics HPU015 is a high powered mobile test and flushing unit designed for flushing and testing using water based fluids.

Features include:

- compact lifting frame;
- Remote compensated piston pump with horsepower controller and load sensors
- Pressure and return line filtration to 5µ

### **Build Specification**

Gross Weight	850kg
Dimensions	L:1.80m, W:1.30m, H:1.27m
Typical Design Life	20 years
Environmental Cert.	Typ5°C to 45°C, Typ. DNV
Cathodic Protection	RP-B401
Electrical Systems	Typ. IECEx certified
Frame / Skid construction	Material: Steel plate AS3678 grade 250/350.
	Welding: AS1554.1 CAT SP
Hydraulic Tube Work	Typ. ASME B31.3
Materials Certification	EN 10204 3.1

### **Additional Pump Information**

#### All blast heat exchanger

• (Not rated for Zone II, can be isolated)



DNV-GL





### **Operating Specifications**

Fluid Types	Water Glycol
Power Input	Electrical, 10m 32A 3Ø Plug
Pump Drive 1	Electro-hydraulic (low press.)
Pump Drive 2	Pneumatic (high press.)
Tank Data	Stainless Steel 225L
Pump 1 Pressure	280bar
Pump 2 Pressure	1300bar
Pump 1 Flow	0 – 30 L / min
Pump 2 Flow	0 – 0.5 L / min

www.pressuredynamics.com

# **ABOUT PRESSURE DYNAMICS**



Pressure Dynamics is an engineering and services contractor specialising in hydraulic and lifting solutions.

Our team of highly skilled project managers, engineers and technicians are committed to collaborating with our clients in providing innovative, quality-assured services and products that deliver superior function, reliability and safety.

When we deliver, we focus on:



Pressure Dynamics International Pty Ltd 234 Barrington Street Bibra Lake WA 6163 Tel: (08) 9473 7277 ABN 65 164 492 433 sales@pressuredynamics.com www.pressuredynamics.com